

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : MXS SILICONE LUBRICANT
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant

1.3. Details of the supplier of the safety data sheet

ATLANTİK AEROSOL ve KİMYA SANAYİ A.Ş.
Fatih Mh. Altinkent Sk. No:4 Tavşanlı Beldesi Altınova
Yalova - TÜRKİYE
T + 90 226 465 72 27 - F + 90 226 465 72 26
info@atlantikkimya.com.tr - www.atlantikaerosol.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Turkey	Ulusal Zehir Merkezi (UZEM) Refik Saydam Hıfızissihha Merkezi Başkanlığı	Cemal Gürsel Cd. No: 18 Sıhhiye Çankaya 06590 Ankara	114	Information is provided to public and medical personnel on poisoning incidents via 114.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Skin sensitisation, Category 1 H317
Reproductive toxicity, Category 2 H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Specific target organ toxicity — Repeated exposure, Category 2 H373
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H-statements: see section 16

Adverse physicochemical, human health and environmental effects : Pressurised container: May burst if heated. Extremely flammable aerosol. Toxic to aquatic life with long lasting effects. May cause damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause an allergic skin reaction.

2.2. Label elements

Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Hazard pictograms (SEA) :



Signal word (SEA) :

Danger

Hazardous ingredients :

n-hexane; (R)-p-mentha-1,8-diene; d-limonene

Hazard statements (SEA) :

H222 - Extremely flammable aerosol.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H336 - May cause drowsiness or dizziness.
H361 - Suspected of damaging fertility or the unborn child.
H373 - May cause damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (SEA) :

P201 - Obtain special instructions before use.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

P251 - Do not pierce or burn, even after use.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face with soap and water thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.

2.3. Other hazards

Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.
Liquefied petroleum gases - LPG	(CAS-No.) 68476-85-7 (EC-No.) 270-704-2	60	Flam. Gas 1, H220 Press. Gas (Comp.), H280
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	30	Flam. Liq. 2, H225 Repr. 2, H361f Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
(R)-p-mentha-1,8-diene; d-limonene	(CAS-No.) 5989-27-5 (EC-No.) 227-813-5 (EC Index-No.) 601-029-00-7	5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenyl methicone	(CAS-No.) 63148-58-3	5	Not classified

Specific concentration limits:

Name	Product identifier	Specific concentration limits
n-hexane	(CAS-No.) 110-54-3 (EC-No.) 203-777-6 (EC Index-No.) 601-037-00-0	(5 =<C < 100) STOT RE 2, H373

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : [In case of inadequate ventilation] wear respiratory protection.
Environmental exposure controls : Avoid release to the environment.



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear
Colour	: Colourless
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

Aspiration hazard : Not classified

MXS SILICONE LUBRICANT	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Before neutralisation, the product may represent a danger to aquatic organisms.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Classification procedure (Chronic aquatic toxicity) : Calculation method

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

MXS SILICONE LUBRICANT	
Bioaccumulative potential	No additional information available

12.4. Mobility in soil

MXS SILICONE LUBRICANT	
Mobility in soil	No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Ozone : Not classified

Other adverse effects : No additional information available






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1950	1950	1950	1950	1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the	Dangerous for the environment : Yes	Dangerous for the	Dangerous for the	Dangerous for the



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

ADR	IMDG	IATA	ADN	RID
environment : Yes	Marine pollutant : Yes	environment : Yes	environment : Yes	environment : Yes
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

- Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

- Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

- Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

- Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200



MXS SILICONE LUBRICANT

Safety Data Sheet

In accordance with the Regulation on Safety Data Sheets Regarding Hazardous Substances and Mixtures published in the Official Journal numbered 29204 on December 13, 2014

Date of issue: 13/02/2019 Version: 0.0

Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

This product doesn't contain any substances that is controlled or prohibited for use according to the Regulation for Reduction of Ozone Depleting Substances published in the Official Journal numbered 27052 on November 12, 2008.

Regulatory reference	: Waste Management Regulation published in the Official Journal numbered 29314 on April 2, 2015 Regulation on Test Methods that will be Applied to Determine the Physicochemical, Toxicological and Ecotoxicological Properties of Substances and Mixtures published in the Official Journal numbered 28848 on December 11, 2013 Regulation on Health and Safety Precautions When Working with Chemical Substances published in the Official Journal numbered 28733 on August 12, 2013 Regulation on Inventory and Control of Chemicals published in the Official Journal numbered 27092 on December 26, 2008 Regulation on Restriction and Prohibition of Hazardous Substances and Mixtures published in the Official Journal numbered 27092 on December 26, 2008 Communiqué on Detergents and Surfactants Used in Detergents published in the Official Journal numbered 27092 on December 26, 2008.
----------------------	--

SECTION 16: Other information

Full text of H-statements

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Safety Data Sheet author's

Name	: İrem BEKTAŞ KART
Certificate number	: GBF-A-0-2732
Contact information	: irem@bekkdanismanlik.com

SDS Turkey

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product